

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 2004046084 A

(43) Date of publication of application: 12.02.2004

(51) Int. Cl. G02F 1/365
G02B 6/16, G02F 1/355

(21) Application number: 2003103650
(22) Date of filing: 08.04.2003
(30) Priority: 15.05.2002 JP 2002140454

(71) Applicant: NATIONAL INSTITUTE OF
ADVANCED INDUSTRIAL &
TECHNOLOGY
ALNAIR LABS:KK
(72) Inventor: SAKAKIBARA YOICHI
TOKUMOTO MADOKA
ACHINAMI HIROTSUGU
KATAURA HIROMICHI
TANAKA YUICHI
MARK KENNETH ZHABORONSKI

(54) OPTICAL TRANSMISSION MEDIUM


(57) Abstract:

PROBLEM TO BE SOLVED: To apply nonlinear optical characteristics of a carbon nanotube to an optical communication field.

SOLUTION: The optical transmission medium 12 obtained by including the carbon nanotube having optical nonlinear characteristics into a nonlinear optical transmission medium is used by incorporating the medium between general optical transmission media (14a and 14b) and by being combined with an optical circulator 16, by which the optical transmission medium is made

usable as an optical fuse (a breaker) to allow the transmission of normal signal light A and, on the other hand, to shut off the transmission of undesirably generated abnormal intensity light.

COPYRIGHT: (C)2004,JPO



12 : CNT含有光伝送媒体 14a, 14b, 14c : 光伝送媒体
16 : 光サイクリュレータ

この発明の実施の形態の説明に供する図



Copyright

(19)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 200404601

(43) Date of publication of application: 12.02.2

(51) Int. Cl. G02F 1/355
G02B 6/16, G02F 1/355

(21) Application number: 2003103650
(22) Date of filing: 08.04.2003
(30) Priority: 15.05.2002 JP 2002140454

(71) Applicant: NATIONAL INSTITUTE OF
ADVANCED INDUSTRIAL &
TECHNOLOGY
ALNAIR LABS:KK
(72) Inventor: SAKAKIBARA YOICHI
TOKUMOTO MADOKA
ACHINAMI HIROTSUGU
KATAURA HIROMICHI
TANAKA YUICHI
MARK KENNETH ZHABORO

(54) OPTICAL TRANSMISSION MEDIUM


(57) Abstract:

PROBLEM TO BE SOLVED: To apply nonlinear optical characteristics of a carbon nanotube to an optical communication field.

SOLUTION: The optical transmission medium 12 obtained by including the carbon nanotube having optical nonlinear characteristics into a nonlinear optical transmission medium is used by incorporating the medium between general optical transmission media (14a and 14b) and by being combined with an optical circulator 16, by which the optical transmission medium is made

usable as an optical fuse (a breaker) to allow the mission of normal signal light A and, on the other hand, to shut off the transmission of undesirably generated abnormal intensity light.

COPYRIGHT: (C)2004,JPO



12: 非線形光学伝送媒体 14a, 14b: 一般光学伝送媒体
16: 光学サイリスタ

この発明の実施の形態の一例を示す図



OrderPatent

DELPHION**RESEARCH****PRODUCTS****INSIDE DELPHION**[Log Out](#) [Work Files](#) [Saved Searches](#)[My Account](#)Search: [Quick/Number](#) [Boolean](#) [Advanced](#) [Der](#)**The Delphion Integrated View**Get Now: ☒ [PDF](#) | [More choices...](#)Tools: [Add to Work File](#) [Create new Work I](#)View: [INPADOC](#) | Jump to: [Top](#)[Email](#)Title: **JP2004046084A2: OPTICAL TRANSMISSION MEDIUM**Country: **JP Japan**Kind: **A2 Document Laid open to Public inspection i**Inventor: **SAKAKIBARA YOICHI;
TOKUMOTO MADOKA;
ACHINAMI HIROTSUGU;
KATAURA HIROMICHI;
TANAKA YUICHI;
MARK KENNETH ZHABORONSKI;**Assignee: **NATIONAL INSTITUTE OF ADVANCED INDUSTRIAL & TECHNOLOGY****ALNAIR LABS:KK**[News, Profiles, Stocks and More about this company](#)Published / Filed: **2004-02-12 / 2003-04-08**Application Number: **JP2003000103650**IPC Code: **[G02F 1/365](#); [G02B 6/16](#); [G02F 1/355](#);**ECLA Code: **G02F1/35D;**Priority Number: **2002-05-15 JP2002000140454**Abstract: **PROBLEM TO BE SOLVED: To apply nonlinear optical characteristics of a carbon nanotube to an optical communication field.****SOLUTION: The optical transmission medium 12 obtained by including the carbon nanotube having optical nonlinear characteristics into a nonlinear optical transmission medium is used by incorporating the medium between general optical transmission media (14a and 14b) and by being combined with an optical circulator 16, by which the optical transmission medium is made usable as an optical fuse (a breaker) to allow the transmission of normal signal light A and, on the other hand, to shut off the transmission of undesirably generated abnormal intensity light.****COPYRIGHT: (C)2004,JPO**INPADOC Legal Status: **None** Get Now: [Family Legal Status Report](#)Family: [Show 3 known family members](#)Other Abstract Info: **None**



[Nominate](#)



[this for the Gallery...](#)



Copyright © 1997-2005 The Tho

[Subscriptions](#) | [Web Seminars](#) | [Privacy](#) | [Terms & Conditions](#) | [Site Map](#) | [Contact U](#)